

DECLARATION OF PERFORMANCE
 No. MW/050C/CE/2024

1. THERMOWOOL ROOF V EXTRA 170

MW-EN 13162-T5- DS (70,-)-DS(23,90)- CS(10)50-TR15-PL(5)650 -WS-WL(P)-MU1- RтF: A1

2. Intended use: Thermal insulation boards for building

3. Manufacturer:

Limited Liability Company "Heat-Insulating Plant "TECHNO"

Having its seat in: LLC «Plant «TECHNO» 18028 Ukraine, Cherkassy, Rizdvyana Street 300

ORIGIN: Ukraine

Tel/fax: +38-(0472)-71-97-97

techno@sweetondale.cz

4. -

5. AVCP 1 (1+3)

6. Harmonized standard: EN 13162:2012+A1:2015

Notified body No. 1023. Institut pro testování a certifikaci, a.s. třída Tomáše Bati 299, Louky, 763 02 Zlín Česká republika/Czech Republic

tel/phone: +420 577601541

7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Declared thermal conductivity at 10 °C, λ_D , W/m ² K	0,038	EN 13162:2012 + A1:2015
Limit deviations Length, Width, mm	$\pm 2/\pm 1,5$ %	
Limit deviations of thickness, mm	T5	
Thickness, (with increments of 10 mm), mm	40-110	
Deviation from squareness, mm/m	< 5	
Deviation from flatness, mm	< 6	
Compressive stress at 10% deformation, kPa	CS(10)50	
Tensile strength perpendicular to faces, kPa	TR15	
Point Load, N	PL(5)650	
Dimensional stability, %:		
-at specified temperature	DS(70,-) less than 1	
-under specified temperature (23oC) and humidity conditions (90%R.H.)	DS(23,90) less than 1	
Reaction to fire, euroclass	A1	
Water Absorption during Short/	WS less than 1	
Longterm Immersion kg/m ²	WL(P) less than 3	
Water vapour transmission, MU	MU1	
Dangerous Substances:	Does not include dangerous substances	

8. Appropriate Technical Documentation and/or Specific Technical Documentation

Signed for and on behalf of the manufacturer by:

 General Director
 LLC «Plant «TECHNO». At Cherkassy on 16.05.2024


Mr. Oleg Khodakivskyi